

AMBIENCE C35T

20W, compact dual tweeter with 3.5" passive radiator subwoofer having both low impedance and 70/100V operation



FEATURES

- **Dual tweeter for crisp highs**
- **Compact design - small diameter and shallow depth**
- **Passive radiator for improved bass response**
- **Suitable for both Public Address and Background music**
- **Rimless design**
- **Aesthetic design with ABS enclosure**

The Alpha Acoustics® AMBIENCE C35T is a small format ceiling speaker suitable for speech and background music which provides excellent performance to size ratio. The speaker has push terminals that enables quick and easy installation. . The dual tweeter enable crisp highs and the passive radiator ensure good bass response in spite of the size. The speaker is suitable for 70/100V operation as well as low impedance application. With the multiple taps available, this speaker will be a perfect fit for commercial audio applications.

AMBIENCE C35T SPECIFICATIONS

Frequency response (-6dB)	100 Hz - 20 kHz
Transducers	LF : 1 X 3.5" HF : 2 X 1" 1 X Passive Radiator
Directivity	120°
Sensitivity	88 dB
Maximum SPL	101 dB
Impedance	8 Ω
Power RMS @ 8 Ω	20W
Power Peak @ 8 Ω	40W
Power @ 100 V	20 / 10 / 5 W
Enclosure material	ABS with metal grille
Dimensions	223 (Dia) X 85(H) mm
Hole cut out size	190 (Dia)
Net weight	1.4 Kg



APPLICATIONS

Shopping Malls | Retail stores | Offices | Hotels

**Specifications subject to change without notice. 01/2023*

Head Office

Alpha Acoustics
Vinecká 1,
293 01 Mladá Boleslav
Czech Republic
info@alphacoustics.com

EMEA Office

Alpha Acoustics DWC-LLC
BUILDING A3, Office No. DLC-BC-A3-3-OSSD6-04
Dubai South Business Center,
Dubai Logistics City
Dubai, United Arab Emirates